

Linssen 40 SL AC

Date: 2-1	-2024	Page	1
ltem D	escription		Phase
1. HULL			
1.2 STAI	NLESS STEEL		
12020.02	Polished stainless steel hinged side ladder integrated into deck rail (Port and Starboard)		1
12055.15	2x Original Linssen Design stainless steel cleats aft from side entrance.		1
12060.01	Original Linssen polished stainless steel bow ladder (removable)		3
12071.01	Stainless steel protection set at side railing entrances and stern (3x)		2
12075.01	Stainless steel steps to saloon deck midships, demountable, finished with anti-slip steps incl. 2 hand grips on saloon deck		2
12155.01	Bathing platform extension made of special quality aluminium ALMG3 powder coated, covered around with special Linssen PVC fendering, finished with solid teak planks and including a base for a support for mounting a tender. The design will be similar as the main platform but having approximately 2/3 of the dimensions of the original platform resulting in an extra length of 60 cm.		2
	Not possible in combination with position(s): 36040.05 Tenderlift electric		
1.3 TECH	INICAL		
13020.05	2x 4 cyl. Volvo Penta Diesel, type D2-75 / ZF 25-H / 2,8 : 1 / 2x 55 kW (75 HP), 3000 rpm Alternator: 2x 115A-12V		1
13070.03	Provisions for simple installation of stabilization system to prevent rolling of the ship. 1 mounting flange welded portside in the hull in the aft cabin in the walk-in closet.		1
13155.01	Mooring facility at bow through stainless steel hawse and stainless steel protection strips		1
13290.01	Heating (blower) at the outside steering position by means of heat exchanger connected to the engine. Equipped with 4x blowers (2x against windscreen windows, 2x under the steering position). The heat exchanger is mounted in the saloon settee including an extra expansion tank for the engine cooling.		1
13300.04	LED deck illumination 4x integrated in deck-box and 2x integrated at steering position		1

Linssen 40 SL AC

20 December 2023

Page 2

Item Description Phase 2. COATING **2.1 COATING & DECK FINISH** 21090.26 Original Linssen SL colour scheme "Haven Grey": 1 Hull : Haven Grey Superstructure : Egg Shell White Waterline : SL bow-up design, Egg Shell White : Black Antifouling Rope fender : Black Canvas color : Sunbrella Marine Steel : "Smoke Grey" tinted Glass windows saloon 21090.27 1 Original Linssen SL colour scheme "Cove Green": Hull : Cove Green Superstructure : Egg Shell White Waterline : SL bow-up design, Egg Shell White Antifouling : Black Rope fender : Black Canvas color : Sunbrella Marine Beige Chine : "Smoke Grey" tinted Glass windows saloon, windscreen 21090.28 Original Linssen SL colour scheme "Fjord Blue": 1 Hull : Fjord Blue Superstructure : Egg Shell White Waterline : SL bow-up design, Egg Shell White : Black Antifouling Rope fender : Black Canvas color : Sunbrella Marine Steel : "Smoke Grey" tinted Glass windows saloon, windscreen **2.2 TEAK DECKS** 22010.01 Original LINSSEN teak deck on front deck and side decks 1 1 22020.01 Original LINSSEN teak deck on aft deck, steps on transom and ventilation-/escape hatch **3. ENGINE COMPARTMENT 3.1 TECHNICAL** 31032.26 Bowthruster finished with proportional control. Stepless control of 1 bowthruster (in combination with proportional stern thruster with parking position on every performance). Including control panel with integrated LCD display for feedback of battery capacity, (rest) functioning time, temperature and system warnings. 31053.05 Electric stern thruster Side Power 24V/100 Kgf (6,3 kW/8,4 HP) incl. 1 2x "Super Cycle" AGM battery 170Ah maintenance-free battery for service net 24 V. 1 31053.25 Electric stern thruster Side Power 24V/100 Kgf (6,3 kW/8,4 HP) incl. 2x. maintenance-free battery AGM 170 AH for service net finished with proportional control. Stepless control with parking position on every performance. Including control panel with integrated LCD display

Linssen 40 SL AC

Ph	escription	n Des
	for feedback of battery capacity, (rest) functioning time, temperature	
	and system warnings.	
	Stabilization system (electric, 230V) to prevent rolling. One stabilizer. Position in Port wardrobe aft cabin.	1130.06
	Attention: System is connected to generatorset and therefore only applicable in combination with generator	
	Only in combination with position(s): Attention:	
	Only possible in combination with generator 13070.03 Provisions for stabiliser(s)	
	Double fuel filter with switch (single).	1190.05
	Double fuel filter with switch (twin)	1200.05
	Compact fuel filter installation. Removes sludge and diesel bacteria from the fuel tank. Also provides for condensation water separation.	1205.01
	App-module for remote switching/controlling the daytime heating. System uses subscription, Free for the first year and €35,- per year	1240.99
	thereafter (by purchasing customer). App control via iPhone or Android device is free to download.	
	Towel radiator in toiletcompartment front cabin electric 230 V. thermostatically controllable	1308.01
	Towel radiator in toiletcompartment aft cabin electric 230 V. thermostatically controllable	1308.21
	Provisions for airco consists of:	1501.00
	- Fitting of cooling pipes incl. distributor	
	- Fitting of power cable chiller + air handlers	
	- Installation of air ducts, outlets and hoses for air intake/supply	1501.01
	Chiller air conditioning in the whole ship through compressor with Softstart, total capacity from 20.000 BTU.	1501.01
	Only in combination with position(s): 31501.00 Provisions for airco	
	OARD WATER SYSTEMS	3.2 ON-BC
	Additional 1x solid plastic MTS on-board water tank on SB-side	2010.20
	without tank measurement with inspection/cleaning opening \pm 220 l.	
	All grey water outlets (sinks and shower-drainage, including aft cabin) connected to holding tank. Including washing machine if chosen.	2100.01
	No fitting of holding tank waste pump	2110.01
	Deck-wash pump, including hose and trigger nozzle with connection at	2150.04
	bathing platform	2150 12
	Deck-wash pump, including hose and trigger nozzle with connection at bathing platform connected to on-board water system	2150.13
	TRICAL & ELECTRONICS	3.3 ELECT
	Cerbo GX linked to the Raymarine Axiom MFD.	3148.15
	Monitor your domestic, shore power and generator status.	
	Control the shore power limit to be used from your helmsman's position	

Linssen 40 SL AC

Page 4

ltem	Descri	ption												Phase
33285.6	9	Group of Solar cha read out	rge c	ontro	ller for	chargi	ing the	e dome						2
33290.1	L3 I 0	Northern continuou separator To contro	Ligh us po r for e	ts 230 wer, i exhau	DV/7 KV integrat Ist gene	V, type ted in s erator.	e M773 shore j	3LW3G power	connec	ction. I		-	S	2
3.4.2	NAVIG	ATION P	АСК	AGES										
Ра	ck	3.4.2.1	BAS	SIC P/	ACKAG	δE								2
34	4090.16	Rudder i	indica	ation	on Ray	marine	e Axior	n displ	ay at st	eering	g positi	on		
34	4125.01	Raymari	ne A	kiom+	⊦ 7 mult	tifunct	tional d	display						
34	4140.03	Navionio	cs Go	ld XLS	9 marin	ne char	rt type	46XG,	West E	urope				
Ра	ck	3.4.2.2	RIV	ER P	ACKAG	GE								2
34	4110.10	Raymari compute which di	er/ru	dder i	indicato	or/com	npass t	transdu	icer) wi	ith pro	otectio	n in ma		
34	4125.01	Raymari	ne Ax	kiom+	- 7 mult	tifunct	tional d	display						
34	4140.03	Navionio	cs Go	ld XLS	9 marin	ie char	rt type	46XG,	West E	urope				
Ра	ck	3.4.2.3	LAł	(E PA	CKAGE	E								2
34	4110.10	Raymari compute which di	er/ru	dder i	indicato	or/com	npass t	transdu	icer) wi	ith pro	otectio	n in ma		
34	4125.07	Raymari and Wi-f log and o	Fi at s	steeri	ng posi	ition. lı	ncludir			•	•		screen	
34	4132.80	Raymari displays	ne Rl	VIK-1(0 remo	te keyp	pad for	r comp	lete tou	uch co	ntrol f	or Axio	m	
34	4140.03	Navionio	cs Go	ld XLS	9 marin	ie char	rt type	46XG,	West E	urope				
Ра	ck	3.4.2.4	SEA	A PAC	KAGE									2
34	4110.10	Raymari compute which di	er/ru	dder i	indicato	or/com	npass t	transdu	icer) wi	ith pro	otectio	n in ma		
34	1125.07	Raymari and Wi-f log and o	Fi at s	teeri	ng posi	ition. lı	ncludir			•	•		screen	
34	132.80	Raymari displays	ne Rl	VK-10	0 remo	te keyp	pad for	r comp	lete tou	uch co	ntrol f	or Axio	m	
34	4140.03	Navionio	cs Go	ld XLS	9 marin	ie char	rt type	46XG,	West E	urope				
34	4160.05	Raymari	ne Q	uantu	ım 2 (D	oppler	r) CHIR	RP rada	r anten	nna, or	n the m	nast		

3.4.3 VIEW PACKAGES

Linssen	Yachts	Option	list
LIIIJJCII	Tuchtu	Option	1130

Linssen 40 SL AC

Item	Description	Phase
3.4.3	.1 Rear view	
34145.	11 1x Raymarine IP day & night net dome video camera on transom for rear view with readout on multifunctional Raymarine display	1
3.4.3	.2 Mooring view	
34145.	 2x Raymarine IP day & night net dome video cameras with readout on multifunctional Raymarine display: - 1x SB and 1x Port on the hull for mooring view 	1
34145.	-	1
3.4.3	.3 Night view	
34800.	Flir M232 Thermic IP camera (320 x 240, 9Hz) with Pan & Tilt and electronic zoom fitted in the mast with read out on multifunctional Raymarine display. The FLIR camera makes the air draft 30 cm higher because of its placement in the mast top.	2
3.4.3	.4 Technology view	
34145.	13 2x Raymarine AX8 thermal and visible light camera in engine compartment for temperature measurement with readout on multifunctional Raymarine display Only in combination with twin engine version	2
34145.		2
34142.	20 Read out engine functions on multifunctional display Raymarine.	3
3.4.3	.5 Underwater view	
34170.	Raymarine RV320 transducer with 3D Downvision Port + SB integrated on multifunctional display Raymarine	1
34145.	on Axiom multifunction display.	2
	Only in combination with position(s): 34943.04 AIS 700	
3.4.4	REMOTE PACKAGES	
34110.	 Raymarine S100 wireless autopilot remote control Only in combination with position(s): 34110.10 p70R Display steering position 	2
34110.		2
31067.	, ,	3
31067.	Remote control for bow (and stern) thruster with proportional control.Control via remote control only on-off.	3

Linssen 40 SL AC

Page 6

em	Description	Phase
31088.20) Hydronautica RMC remote control for engine(s), bow and stern thruster.	
	Only in combination with position(s):	
31088.22	31053.05 Stern thruster 100 Kgf Hydronautica RMC remote control for engin(es) and bow-/sternthruster finished with proportional control. For using the bow and stern thruster via the RMC, you have to tune the desired performance in the control panel. By doing so, you can easily cruise sidewards by using the bow and stern thruster simultaneous.	:
	Only in combination with position(s): 31032.26 Bow thruster electric 120 kgf 31053.25 Stern thruster 100 kgf	
3.4.5 (COMMUNICATION PACKAGES	
34190.09	Raymarine Ray90 VHF with Class D "Digital Selective Calling" (DSC) at steering position including antenna in Mast	2
34190.10) Extra wireless handset VHF incl. charging station	
34200.10	Communication tool for 2 persons by means of 2 walkie-talkies with headset	:
34943.04	AIS 700 transponder/receiver (Automatic Identification System) integrated on radar/chartplotter display. Attention: MMSI-number required. Attention: Only in combination with VHF installation	
3.4.6 (OTHER NAVIGATION INSTRUMENTS	
34120.23	Wind Vane" wind transducer for wind direction and wind speed. Read out on Axiom display.	:
34135.06	Second Raymarine Axiom+12, 12" multifunctional colour display with touchscreen and Wi-Fi at steering position. Including read out from echosounder, log and outside water temperature.	:
3.5 EX	TERIOR EQUIPMENT HULL	
35010.02	Magnesium anodes (for fresh water)	2
35010.02	Zinc anodes (for salt water)	:
35092.32	Electric anchor winch 1200W/24V. mounted above deck with integrated stainless steel anchor rollers and anchor rail with 50m. 10 mm. anchor chain and 20 Kg. Bruce-anchor.	:
35110.03	8 Wireless windlass control and chain counter	2
35120.12	High gloss polished stainless steel Bruce-anchor 20 kg. AISI-316	:
35140.04	80m. x 10 mm. anchor chain, according DIN 766	
35140.13	50 m. 10 mm. stainless steel anchor chain Only in combination with position(s): 35092.32 Electric anchor winch Tiger	
35140.14	-	

3.6 LINSSEN YACHTS TENDER SOLUTIONS

Linssen 40 SL AC

Pha	escription	em De
	Passarele Opac Mare type 4999/24 with a minimal length of 1575 mm and maximal length of 2425 mm and a loading capacity of 230 kg. The passarelle will be mounted at the position of the first step of the bathing platform and will remain the 'sideway- access' function of the stern stairs. The passarelle will be finished with a teak grating, automatic stanchions and 2x wireless remote controls	36020.03
	Stainless steel snap davit system, with universal tender fastening.	36040.01
	Linssen Yachts electric stainless steel dinghy lift installation on bathing platform. Lifting capacity 250 kg. incl. remote control.	36040.05
	Fitting of customer supplied tender.	36048.01
	Outboard engine fastening bracket against stern (Max. 8 HP)	36100.01
	RIOR EQUIPMENT SUPERSTRUCTURE	3.7 EXTER
	Extend windscreen wiper installation with synchronous and 3 step interval function. In the interval mode, the wipers run synchronously and are self-parking.	37020.50
	Original Linssen Design mast powder coated in colour superstructure. Short modell (beneath windscreen)	37070.06
	Electric mast lowering system, incl. control at steering position.	37080.08
	Not possible in combination with position(s): 37070.06 SL-mast short (1,4 mtr)	
	2nd helm-seat in Maglia Uyuni, on stainless steel adjustable support.	37110.38
	Folding teak directors chair. Black upholstery and naturel teak wood	37111.01
	Electrically-adjustable Linssen Design comfortable helm-seat, height adjustabl with matching upholstery. Horizontally manually adjustable	37120.02
	Deck lighting with 2 lights at mast	37130.01
	Automatic searchlight with stainless steel housing on saloon deck, with control at the steering position	37140.05
	Automatic searchlight with stainless steel housing in the mast, with control at the steering position	37140.06
	Set of fender baskets to fore deck: Double Port & SB ø300 mm, foldable	37170.14
	Luxury teak table incl. joint (outside)	37230.01
	Teak table with luxurious high gloss painting in 8 layers	37230.90
	Teak table with luxurious satin gloss painting in 3 layers	37230.91
	Solid teak entrance door, varnished	37271.01
	DOWS	3.8 WIND
	Double-glazed "Smoke grey" tinted windows in the saloon (incl. entrance door) with grey thermal insulated profile (Thermic Line). Attention: The sliding window will be finished in single glass	38031.31
	Hinged window in Port forward saloon, with grey profiles and "Smoke grey" tinted glass	38061.32
	Hinged window in Port forward saloon, with grey insulated profiles and "Smoke grey" tinted (Thermic Line) double glass	38061.36

Linssen 40 SL AC

Item	Description	Phase
38071.32	Aluminium fixed Port centre window in saloon, with grey profiles and "Smoke grey" tinted glass	1
38071.35		1
38071.36	5 Port sliding window in the saloon, finished in double glass (Thermic Line), incl. grey thermal insulated profile and "Smoke grey" glass	1
38081.32	Aluminium sliding window middle in saloon at Starboard side, with grey profiles and "Smoke Grey" tinted glass	1
38081.36	5 Stbd sliding window in the saloon, finished in double glass (Thermic Line), incl. grey thermal insulated profile and "Smoke grey" glass	1
4. INTERI	OR	
GENER	RAL	
40040.02	2 Original Linssen maintenance friendly ship's floor, teak color with black striping.	2
4.1 AF	Τ CABIN	
41010.02	Stylish/high quality floor covering in rear cabin on second floor level next to bed.	3
41051.90	D Mirror in aft cabin on aft bulkhead	2
4.2 SA	LOON & GALLEY	
42031.03	3 Elegant saloon table, high model Not possible in combination with position(s): 42035.03 Saloon table low	2
42033.02	 Low coffee table model, pouf / tray combination Not possible in combination with position(s): 42035.03 Saloon table low 	2
42073.92	Extra drawers in dinette accessible by longitudinally adjustable dinette table	2
4.3.1	FRONT CABIN AND GUEST CABIN	
43010.02	Stylish/high quality flooring in front cabin on second floor level next to bed.	3
43101.02	 1 bed at Port side against wall (width 90 to 100 cm) 57 Ltr. refrigerator, accessible from guest cabin, fitted under dinette settee 	2
	 Reading light above bed against wardrobe Not possible in combination with position(s): 52062.14 	
43101.03	 Layout guest cabin, version 2: Desk, drawers on the left side and additional cupboard under the work top Design Hocker in leather 57 Ltr. refrigerator, accessible from guest cabin, fitted under dinette settee 	2
	- Reading light above desk	

Linssen 40 SL AC

Pha	escription	tem Des
	- 2x 230 V. and 1x USB sockets on work top	
	Not possible in combination with position(s):	
	52062.14	
	Bed guest cabin finished with removable joint incl. mattress for double bed function	43101.99
		5. FINISH
	TING & SOCKETS	5.1 LIGHT
	Luxurious LED reading lights (2x) in the front cabin	51080.11
	Luxurious LED reading lights (2x) in the guest cabin	51090.11
	Attractive indirect lighting in saloon	51100.01
	Attractive indirect lighting in the FC and AC heads	51100.02
	Indirect lighting in all steps of saloon stairs	51110.02
	Indirect lighting in all steps of front cabine stairs	51110.03
	Indirect lighting in all steps of after cabine stairs	51110.04
	USB socket in FC portside and AC starboardside for charging mobil equipment.	51400.05
	USB socket in steering position, FC, guest cabin and AC for charging mobil equipment.	51400.11
	12 V. and 230 V. socket in front cellar	51595.01
	7x 230V sockets in English version	51607.02
	7x 230V sockets in Swiss version	51607.03
	230 V. socket in the forward cabin on SB-side	51615.01
	3x 230 V. sockets respectively in FC, engine compartment and after cabine for winter heating. Only to be used with shore power or generator on.	51625.01
	230 V. socket in the guest cabin	51630.01
	230 V. socket in the galley	51640.01
	230 V. socket in saloon (Port-side aft)	51655.01
	230 V. socket in the saloon (Stbd aft)	51665.01
	230 V. socket in the aft cabin (Stbd side)	51675.01
	230 V. socket at steering position, SB side splash resistant	51700.11
	EY	5.2 GALLE
	High gloss polished stainless steel towel rail at refrigerator door	52031.02
	Cooling drawer, 30 liter, fitted in front cellar.	52062.14
	2nd Cooling drawer, 30 liter, fitted in front cellar.	52062.15
	Cooling Tray, 30 liter, built-in at the end face of the rear half saloon settee	52062.01
	Freezer 40 ltr. in the cellar	52065.14
	Not possible in combination with position(s): 32010.20 Additional watertank	
	230V. washer/dryer combination, fitted in the forward cabin shower compartment	52100.02

Linssen 40 SL AC

tem	Description	Phase
52140.0	 230V. induction hob with touch control. 1 x 1200 W. cooking zone, 1 x 1600 W. cooking zone Attention: 	:
	Only possible in combination with generator	
52140.0	2 230V. induction hob, stainless steel, with touch control. 1 x 1200 W. cooking zone, 2 x 1800 W. cooking zone, 1 x 2200 W. cooking zone	:
	Attention:	
	Only possible in combination with generator	
52080.0	Capacity: 6 covers.	:
	Not possible in combination with position(s): 52220.02 Microwave/oven/grill 42 I. 52230.01 Oven (gas)	
52220.0	2 230V. stainless steel 42 I. microwave/oven/grill combination. Temperature range 30-250 degrees. 90-1000W microwave power. Fitted in the galley next to the sink.	:
	Not possible in combination with position(s): 52080.03 Dishwasher 6 covers 52230.01 Oven (gas)	
52230.0	1 Stainless steel oven (gas). Fitted in the galley next to the sink	
	Not possible in combination with position(s): 52080.03 Dishwasher 6 covers 52220.02 Microwave/oven/grill 42 I.	
5.3 SA	NITARY FITTINGS	
53010.1	In the FC bathroom cabinet integrated 6-litre waste bin with stainless steel soft-close waste flap	
53010.9	0 Full-length mirror in the FC toilet compartment at entrance door to the front cabin	
53015.1	In the AC bathroom cabinet integrated 6-litre waste bin with stainless steel soft-close waste flap	
53015.9	0 Full-length mirror at the inside of the toilet door in the AC	
53015.9	6	
53090.0	1 Shower door in aft cabin shower	:
53130.0		:
53140.0	3 Electrical toilet in the aft cabin, with sea water rinsing	
5.4 Al	JDIO / VIDEO	
54010.5	DAB+ radio module and antenna in the mast for digital radio	:
54010.9	0 Fusion RA70N expansion kit with usb port for data transfer + control via the multi-function display in steering position.	:
54200.0	1 Primary TV connection in saloon Port TV cupboard, incl. extra 230V. socket	:
54210.0	1 Supplementary TV connection in aft cabin, incl. extra 230V. socket	:
54250.0	1 Glomex TV-antenna on mast, suitable for analogue & digital reception. Suitable for DVBT-T2 network.	:

Linssen 40 SL AC

ltem	Description	Phase
54286.02	Provisions for putting a satellite tv-antenna on deck manually: deck socket against the mast incl. cables in tv-cabinet in saloon	2
54400.03	3 32" (81cm) LED TV with integrated DVB-T2 & DVB-S tuner fitted and connected in foldable back part of the dinette settee in the saloon at Port side	3
54410.03	3 32" (81cm) LED TV with integrated DVB-T & DVB-S tuner in aft cabin	2
54610.0	5 Preparation consisting of extra 230V socket in saloon next to TV cabinet and HDMI cable from TV	3
54900.0	5 Teltonika 4G LTE router with Wifi Access Point and antenne in the mast	2
5.5 VE	NTILATION	
55010.02	1 Mosquito screen in forward Starboard hinged saloon window	3
55020.02	1 Mosquito screen in forward hinged saloon window, Port side	3
55030.02	1 Integrated mosquito screen in Port sliding saloon window	1
55040.02	1 Integrated mosquito screen in Stbd sliding saloon window	1
55090.02	2 Rain protection covers and mosquito screens for the forward cabin port-holes (6x)	3
55110.02	1 Rain protection covers and mosquito screens for the aft cabin port-holes (6x)	3
55130.02	1 Combined blind/mosquito screens for panorama/escape hatch in forward cabin deck-head	2
55135.02	1 Combined blind/mosquito screens for cabin and head ventilation/escape hatch	2
55150.02	1 Combined blind/mosquito screens for panorama/escape hatch in the aft cabin deck-head	2
55155.02	1 Mosquito screen for sliding hatch at the entrance door (with magnets)	3
5.6 IN	TERIOR UPHOLSTERY	
56031.9	6 Additional back cushions saloon settee against the galley	3
56073.00	5 Design stool finished in Mocka Rock	3
56073.9	7 ?	2
56078.0	5 Cherry wood cube-shaped pouffe, with tray including seat cushion in Mocka Rock	2
56101.02	2 Mattrass 2x 1 pers.in front cabin type Combispring 14 cm.	3
56131.02	2 Mattrass 2x 1 pers. in aft cabin type Combispring 14 cm.	3
56161.02	2 Mattrass 2x single person in guest cabin type Combispring 14 cm.	3
56161.1	Mattrass 2x single person in guest cabin type coldfoam 14 cm. with layer in foam in two hardness grades	3
56321.03	Plissé blinds in the saloon, manual controlled.	2
56401.13	the entire ship	3
	Only in combination with position(s): 56401.15 Interior package duvets and pilows	
56401.1	5 Interior duvets and pillows set	3

Linssen 40 SL AC

ltem	Description	Phase
5.7 E)	(TERIOR UPHOLSTERY	
57095.0	6 2x Comfort Seat in Maglia Uyuni	3
5.8 EC	QUIPMENT	
58022.0		3
58023.0		3
58024.0	1 Additional 40 m mooring line, supplied with on board inventory	3
58050.0	2 Safe A4 size, with combination lock, in the cabinet middle cabin	2
58060.0	the saloon settee and connection for the hose.	2
	Equipped with thermal protection and softstart for inverter use. Delivery including extendable hose (from 1,5 to 9 m.), luxury brushes and 3 vacuum bags	
58070.0	1 Foldable ironing board, stored in wardrobe guest cabin incl. 230 V socket	2
58075.0	1 Removable clothes rail in guest compartment across the beds	2
58075.0	2 Removable clothes rail in shower compartment front cabin	2
58080.0	1 8 hooks at various positions in the yacht. Positions to be determined during the hand over. Fitted during the 25-hours inspection.	3
58100.0	1 2 high gloss polished stainless steel support next to the mast for biclycles parking	2
58100.1	Stainless steel high-gloss polished bicycle parking bracket on bathing platform. Suitable for 2 bikes. Position is from the center to maximize passageway	3
	Not possible in combination with position(s): 36020.03 Opac Mare type 4999/24 36040.05 Tenderlift electric	
5.9 C/	ANVAS & COVERS	
59030.0	1 Cabrio closed model over the complete aft deck, Sunbrella Marine beige. The side- and back parts can be opened by a zip-fastener.	3
59017.0	1 Drop down system to reduce the draft of the standard cabrio	3
59080.0	4 Cover for entrance door including sliding hatch Sunbrella Marine steel Grey	3
59090.0	1 Cover for helm-seat, Sunbrella Marine beige.	3
59090.0	4 Cover for helm-seat Sunbrella Steel Grey	3
59090.3	4 Cover for second helm-seat Sunbrella Steel Grey	3
59130.0	1 Cover for steering console Sunbrella Marine beige	3
59200.1	Sun cover around saloon windows finished in screen cloth (excluding entrance door/window) incl. mounting, colour beige	3
59200.1	2 Sun cover around saloon windows finished in screen cloth (excluding entrance door/window) incl. mounting, colour white	3

Linssen 40 SL AC

ltem	Desci	ription	Phase
6. COI	MMISSIC	DNING & HAND OVER	
6.0	GENERA	AL CONTRACTOR OF CONT	
6.1	TRANSP	ORT/WINTER STORAGE	
6101	0.01	Cradle (completely coated)	3
6101	0.06	Compile documents for export and obtain a temporary residence permit of up to 18 months in the EU. (Only possible for residents from outside the EU)	3
	Pack	1 Comfort package	1
	12020.02	Polished stainless steel hinged side ladder integrated into deck rail (Port and Starboard)	
	22020.01	Original LINSSEN teak deck on aft deck, steps on transom and ventilation-/escape hatch	
	31053.05	 Electric stern thruster Side Power 24V/100 Kgf (6,3 kW/8,4 HP) incl. 2x "Super Cycle" AGM battery 170Ah maintenance-free battery for service net 24 V. 	
	31067.01	Remote control for bow (and stern) thruster	
	35092.32	2 Electric anchor winch 1200W/24V. mounted above deck with integrated stainless steel anchor rollers and anchor rail with 50m. 10 mm. anchor chain and 20 Kg. Bruce-anchor.	
	37230.01	Luxury teak table incl. joint (outside)	
	58080.01	8 hooks at various positions in the yacht. Positions to be determined during the hand over. Fitted during the 25-hours inspection.	
	Pack	2 Ventilation package	1
	13290.01	 Heating (blower) at the outside steering position by means of heat exchanger connected to the engine. Equipped with 4x blowers (2x against windscreen windows, 2x under the steering position). The heat exchanger is mounted in the saloon settee including an extra expansion tank for the engine cooling. 	
		Integrated mosquito screen in Port sliding saloon window	
		2 Rain protection covers and mosquito screens for the forward cabin port-holes (6x)	
		Rain protection covers and mosquito screens for the aft cabin port-holes (6x)	
		Combined blind/mosquito screens for panorama/escape hatch in forward cabin deck-head	
		Combined blind/mosquito screens for cabin and head ventilation/escape hatch	
	55150.01	Combined blind/mosquito screens for panorama/escape hatch in the aft cabin deck-head	

Linssen 40 SL AC

n	Descri	iption	Phase
	Pack	3 Le Chef package	2
	33290.13	Northern Lights 230V/7 KW, type M773LW3G generator. Intercooling, continuous power, integrated in shore power connection. Incl. water/gas separator for exhaust generator. To control with a control panel with operating hours.	
	52062.01	Cooling Tray, 30 liter, built-in at the end face of the rear half saloon settee	
	52140.02	230V. induction hob, stainless steel, with touch control. 1 x 1200 W. cooking zone, 2 x 1800 W. cooking zone, 1 x 2200 W. cooking zone	
	52220.02	230V. stainless steel 42 l. microwave/oven/grill combination. Temperature range 30-250 degrees. 90-1000W microwave power. Fitted in the galley next to the sink.	
	Pack	4 Traveller package	2
	33290.13	Northern Lights 230V/7 KW, type M773LW3G generator. Intercooling, continuous power, integrated in shore power connection. Incl. water/gas separator for exhaust generator. To control with a control panel with operating hours.	
	52100.02	230V. washer/dryer combination, fitted in the forward cabin shower compartment	
	Pack	5 Media package	2
	54200.01	Primary TV connection in saloon Port TV cupboard, incl. extra 230V. socket	
	54250.01	Glomex TV-antenna on mast, suitable for analogue & digital reception. Suitable for DVBT-T2 network.	
	54400.03	32" (81cm) LED TV with integrated DVB-T2 & DVB-S tuner fitted and connected in foldable back part of the dinette settee in the saloon at Port side	
	Pack	6 Safety package	2
	34190.09	Raymarine Ray90 VHF with Class D "Digital Selective Calling" (DSC) at steering position including antenna in Mast	
	34943.04	AIS 700 transponder/receiver (Automatic Identification System) integrated on radar/chartplotter display. Attention: MMSI-number required. Attention: Only in combination with VHF installation	
	37020.50	Extend windscreen wiper installation with synchronous and 3 step interval function. In the interval mode, the wipers run synchronously and are self-parking.	
	59017.01	Drop down system to reduce the draft of the standard cabrio	
	Pack	7 Luxury package	2
	35120.12	High gloss polished stainless steel Bruce-anchor 20 kg. AISI-316	
	37080.08	Electric mast lowering system, incl. control at steering position.	
	52062.01	Cooling Tray, 30 liter, built-in at the end face of the rear half saloon settee	

Linssen 40 SL AC

Phas	Description	
	Shower door in aft cabin shower	
	8 Atmosphere/lighting package	Pack
	4 LED deck illumination 4x integrated in deck-box and 2x integrated at steering position	
	1 Deck lighting with 2 lights at mast	37130.01
	1 Luxurious LED reading lights (2x) in the front cabin	51080.11
	1 Luxurious LED reading lights (2x) in the guest cabin	51090.11
	1 Attractive indirect lighting in saloon	51100.01
	2 Attractive indirect lighting in the FC and AC heads	51100.02
	2 Indirect lighting in all steps of saloon stairs	51110.02
	3 Indirect lighting in all steps of front cabine stairs	51110.03
	4 Indirect lighting in all steps of after cabine stairs	51110.04
	9 Power package	Pack
	5 USB socket in FC portside and AC starboardside for charging mobil equipment.	
	1 USB socket in steering position, FC, guest cabin and AC for charging mobil equipment.	
	1 230 V. socket in the forward cabin on SB-side	51615.01
	1 230 V. socket in the guest cabin	51630.01
	1 230 V. socket in the galley	51640.01
	1 230 V. socket in saloon (Port-side aft)	51655.01
	1 230 V. socket in the saloon (Stbd aft)	51665.01
	1 230 V. socket in the aft cabin (Stbd side)	51675.01
	1 230 V. socket at steering position, SB side splash resistant	51700.11