

Linssen Yachts Standard Equipment Linssen Grand Sturdy 500 Sedan

Item	Description	Page 1

D	Λ	c	IC	\mathbf{r}	Λ7	ГА
D.	н	.3	ıL	u	А	ΙА

DASIC DAIA			
01010.05	Construction Bottom/hull/decks/superstructure Weight/displacement	: SPH®(patent pending) (Softchine Prestressed Hul : 6/5/4/5-4 mm. : ±25.000 kg / ±25 m³	
01020.05	LOA x beam x draft Length hull Length over deck Length waterline Minimum air draft Headroom FC/saloon	: ± 15.50 x 4.65 x 1.20 m. : ± 14 m. : ± 13.90 m. : ± 12.95 m. : ± 2.75 m. : ± 2.00/2.0.5 m.	
01030.13	CE-classification Number of max. recommended persons	: B (sea) :12	
13020.20	Engines Alternator	: 2x 4 cyl. Mercury Diesel, type MD2.0L ZF 25-H / 2,8 : 1 2x 84 kW (115 HP), 3000 rpm : 2x 110A-12V	
03040.01	Fuel tank capacity Water tank capacity Holding tank capacity	: ± 2x 750 ltr. : ± 720 ltr. : ± 400 ltr.	
42001.01	Spacious saloon with U-settee, low saloon table and galley at Port side. Folding dinette/desk with 2 design stools and inside steering position including steering bench at SB-side.		
42099.99	Additional work surface in the galley through cherry wood folding part next to hob		
43001.01	Forward cabin with double berth and cupboards, separate toilet and shower compartment. Guest cabin with 2 single beds, one bed can be slided, so it can be used as a double bed with drawer and linen cupboard		
43045.01	Niche on Port side in the forward cabin with plex	iglas shelves.	

1. HULL

1.1 EXTERIOR

11015.01	Hull constructed in accordance with the Linssen Yachts $\ensuremath{SPH}^{\ensuremath{\$}}$ (patent pending) construction method
11060.03	Linssen e-Variodeck® (electric sliding roof) in the saloon with integrated cassette mosquito screen/blackout blind
11065.02	Longtop, saloondeck width (small), insulated and finished with ceiling and integrated LED dimmer lights.
11068.01	Selfdraining cockpit with functional drain system
11070.01	Integrated cockpit settee U-shaped with teak top
11080.02	Stern door (SB and Port) to bathing platform
11085.02	Doors in the cockpit at Starboard and Port side

Linssen Grand Sturdy 500 Sedan

S

deck on gangways from transom to sliding doors

3

Linssen Yachts Standard Equipment

Linssen Grand Sturdy 500 Sedan

Item Description Page 3. ENGINE COMPARTMENT 3.1 TECHNICAL 31011.23 Linssen Yachts "hydrolubricated" propeller shaft installation 31021.21 Engine/shaft connection through homokinetic coupling and thrust bearing 31025.22 Low noise propellers 31034.02 Bow thruster 400V/7,5 kW. Powered by the generator, long switching time possible, incl. soft start. Bow thruster can deliver a permanent power of 7.5KW and a peak power of 11KW. 31054.02 Stern thruster thruster 400V/7,5kW. Powered by the generator, long switching time possible, incl. soft start. Stern thruster can deliver a permanent power of 7.5KW and a peak power of 11KW. Twin electronic engine controls at steering position 31080.03 31090.03 Hydraulic steering 31093.02 Stainless steel steering wheel with teak rim, at inside steering position Fuel tanks of advanced design with inspection/cleaning hatch 31145.21 31161.03 Magnetic level gauge in fuel tanks for direct volume indication 31180.05 Separate second (1 x on engine) fuel filter with water separator, per engine 31210.02 Remote fuel supply cut-off to engines from dinette settee 31300.01 Linssen Yachts per cabin thermostatically controlled warm water heating with radiators in the forward cabin, guest cabin, dinette/saloon, aft cabin and wheelhouse. 31307.01 Radiator in front cabin toilet compartment. Thermostatically controlled. Radiator in additional front cabin toilet/shower compartment. Thermostatically controlled. 31307.02 31315.01 Lighting with ir-sensor under cockpit floor 31331.01 Entrance engine compartment by folding ladder between the engines. 31700.03 Automatic fire extinguishing in engine compartment 31750.01 Linssen super sound insulation package consisting of a sound absorbent insulation and a non vibration package. 3.2 ON-BOARD WATER SYSTEMS 32010.13 Automatic pressurized water system (incl. solid PVC water tank with inspection/cleaning hatch), incl. level indicator 32020.01 2 Automatic pumps including expansion reservoir for water system 32050.04 Hot water system (60 litre calorifier) 32060.01 230 V./800W immersion heater in calorifier 32080.20 Fully automated biological blackwater treatment installation using micro-organisms. No unpleasant odours; no use of chemicals that are harmful to the environment. Bacterial strains remove the waste products from the residual water. After treatment, the purified water is pumped out through a sediment filter and a UV filter below the water line. The water to be discharged is free of residues and bacteria. The ENTERON system has type approval in accordance with IMO/MARPOL standards and is compliant in all of the 175 IMO member states that maintain this standard for the discharge of black water. 32095.01 All grey water outlets (sinks and shower-drainage) discharge directly overboard Drain pump(s) shower(s) finished with switch-off delay 32150.04 Deck-wash pump, including hose and trigger nozzle with connection at bathing platform 32190.01 Electric bilge pump installations placed in bilges of aft cabin, forward cabin and engine

room. Equipped with float switch & alarm (3x 100L/min. pumps)

Linssen Grand Sturdy 500 Sedan

Item	Description Page
32200.0	Additional loose electric bilge pump provided, with discharge tube and supply cable
3.3 EL	ECTRICAL & ELECTRONICS
33020.0	1 Electric domestic 12 V. with automatic main fuse and separate fuses for all users
33022.0	Linssen Yachts ICCESS main switchboards, 1x in saloon and 1x at steering position, for control of key functions and reading of fluid levels
33030.0	230V. /16Amp shore power connection, incl. galvanic insulator, earth leakage circuit breaker and automatic fuse protected end groups with indication and shore power cable (25 metres)
33180.0	Starting circuit 12V. with 2 x maintenance free "Super Cycle" AGM-battery.
33090.0	Domestic 12V with 4 Lithium Iron Phosphate (LFP) batteries 200Ah.
33229.0	Domestic net equipped with remote-controlled main switch
33271.0	Automatic battery charger/invertor type Victron Quattro 12/3000 with battery monitor. The battery charger has a maximum charging current of 120A, the maximum output power of the inverter is 3000W.
33285.7	Group of solar panels of 6x 160Wp on part of the longtop. Connected to a Victron Smart Solar charge controller for charging the domestic batteries. Can be read out on the Victron Color GX panel.
33295.0	Generator Northern Lights 400 V/16,0 kW. Priority switch shore power/generator and reverse. Start/stop on steering position.
3.4 IN	ISTRUMENTS & NAVIGATION
34010.0	2 x engine instrument panels with rev.counter, engine hour meter and multifunction meter with voltmeter with alarm, temperature gauge with alarm and oil pressure gauge with alarm
34030.0	2 Compressor horn with control at steering position
34050.0	Government approved LED navigation lights: Starboard and Port side on superstructure, stern light, top light in mast and anchor light
3.4.1	NAVIGATION INSTRUMENTS
34110.1	Raymarine autopilot with p70RS display at steering position (incl. course computer/rudder indicator/compass transducer) with protection in mast which disengages autopilot during AUTO operation if mast is folded.
34125.0	Raymarine Axiom+12RV, 12" multifunctional colour display with touchscreen and Wi-Fi at steering position. Including read out from echosounder, log and outside water temperature.
34132.8	Raymarine RMK-10 remote keypad for complete touch control for Axiom display.
34140.0	Navionics Gold XL9 marine chart type 46XG, West Europe
3.4.5	COMMUNICATION PACKAGES
34190.0	9 Raymarine Ray90 VHF with Class D "Digital Selective Calling" (DSC) at steering position including antenna in Mast
3.4.6	OTHER NAVIGATION INSTRUMENTS
34135.0	Second Raymarine Axiom+12, 12" multifunctional colour display with touchscreen and Wi-Fi at steering position. Including read out from echosounder, log and outside water temperature.
3.5 EX	CTERIOR EQUIPMENT HULL
35010.0	Magnesium or zinc anodes (depending on cruising area)
35030.0	Original Linssen synthetic-fibre rope fender, with stainless steel stretcher (Beige colour)

Linssen Grand Sturdy 500 Sedan

Item	Description Page	5
35040.01	Ships name on bow and stern. Port of Registry and Registration number on stern in colour of the waterline Bow letter type; Snell Roundhand. Stern letter type; VAG	
35090.04	Lewmar VX-series, type VX3 Heavy Duty electric anchor winch, with integrated stainless steel anchor rolls, anchor rail and deck switches.	
35120.02	20 kg. galvanized Bruce-anchor	
35140.03	50m. x 10mm. anchor chain, according DIN 766	
3.7 EXT	TERIOR EQUIPMENT SUPERSTRUCTURE	
37030.02	Stainless steel windscreen wiper installation in saloon SB and middle, with touch control suitable for 2 speeds, self-parking, 3- positions interval on 25, 50 and 75% and wish-wash. Incl. integrated choice for synchronise the windscreen wipers at low speed	
37060.02	Window spray-installation saloon for two wipers	
37070.02	Original Linssen Design mast, with double yard, on saloon deck powder coated in superstructure colour, finished with "eyes" and cleats between the yards for flag lines	
37075.02	Stainless steel mast stays with quick release system	
37080.08	Electric mast lowering system, incl. control at steering position.	
37230.01	Fixed luxury teak table with 2-piece folding joint with quick release at bench on aft deck with stainless steel base.	
37271.12	Entrance door coated in superstructure colour	
37272.11	"Linssen slide and pop-out-door (LSP®)", watertight sliding door in saloon on port and SB-side, coated in superstructure colour, with special lip-seal developed by Linssen	
3.8 WII	NDOWS	
38030.01	Double-glazed "Summer Green" tinted windows in the saloon with thermal insulated profile (Thermic Line).	
38060.36	Front hinged window Port side with green tinted glass in the saloon, can be opened and closed electrically. With grey thermal insulated profile (Thermic Line). Incl. mosquito screen, fitted on the outside with magnets	
38300.08	8 x opening port-holes in the forward cabin, with plain acrylate	
38405.02	2x Aluminium ventilation/escape hatch, with clear acrylic in the forward cabin, incl. blind rouleau/curtain with integrated screen.	
38412.01	Aluminium ventilation/escape hatch, clear acrylic in centre cabin and toilet compartment.	
4. INTERIO	OR CONTRACTOR CONTRACT	
GENER	AL	
40010.01	Linssen panels FPS® (Floating Panel System, Patented)	
40020.03	Interior constructed of high-end okoumé panelling with cherry finish	
40025.14	Interior and exterior style "Classic Traditional": Classic modesty. Stylish elegance through soft beige shades.	
40030.02	Deck-head lining in elegant vinyl finish panels	
40040.02	Original Linssen maintenance friendly ship's floor, teak color with black striping.	
40050.02	High gloss stainless steel fittings in all compartments	
40060.02	High gloss stainless steel door and locker furniture, with push-button catches	
4.1 OPI	EN COCKPIT	

Storage system under the cockpit floor. Executed as cabinet wall 3 modules on SB

folding crates 400x300x200mm.

and 3 modules at Port side. Including 8 plastic storage boxes 400x300x200mm and 2

41141.97

Linssen Grand Sturdy 500 Sedan

Item	Description	Page	6
4.2 S	ALOON & GALLEY		
42011.	Hatch above engine room for easy access and inspection of this room.		
42021.0	O1 Comfortable L-shaped saloon settee with integrated storage space		
42035.0	03 Elegant saloon table, low model		
42037.	O1 Saloon table top with flush leather panel.		
42061.	01 Walnut wood dashboard finished in real leather, at SB side		
42081.	01 U-shaped galley with cupboards and drawers		
42092.	03 U-shaped galley worktop finished with original Corian®		
42141.0	Punctional storage space in forward section, equipped with 6 storage bo	exes and lighting	
4.3.1	FRONT CABIN AND GUEST CABIN		
43010.0	O1 Stylish/high quality flooring in front cabin on second floor level next to b	oed.	
43021.0	Double berth with slatted base and 2 drawers		
43031.0	01 ?		
43041.0	01 ?		
43043.0	Large wall cabinet in the FC on the SB side. The cabinet is equipped with automatic lighting, adjustable and removable shelves and fiddle rails.	1	
43101.0	Two single berths in the guest cabin, incl. drawer under Stbd berth. The be converted into one double bed	beds can	
43121.	O1 Spacious linen cupboard in guest cabin		
4.3.2	SHOWER AND HEADS COMPARTMENTS		
43062.	O2 Toilet/shower walls FC in high quality Formica wall finishing		
43071.	Integrated washbasin surface mounted in front toilet-compartment van finished in original Corian®	ity unit. Worktop	
43082.0	O2 Shower in the FC finished in high quality HPL wall finishing		
43082.	Shower tray front cabin in corian designed with grooves for water drains	age	
43082.0	O1 Guest shower at portside in the FC finished in HPL finish		
43081.	11 Storage space in the toilet compartment FC		
43081.	Corian shower tray in guest wet room in the forward cabin, 3-dimension optimal water drainage.	ally shaped for	
43081.	Integrated washbasin surface mounted in front toilet-compartment van finished in original Corian®	ity unit. Worktop	
43200.0	Shower in guest bathroom with built-in Grohe shower mixer, thermostar including sliding wall bar. 3-dimensionally shaped Corian shower tray for drainage.	•	

Linssen Grand Sturdy 500 Sedan

Description Item Page

5. FINISH

5.1 LIGHT	TING & SOCKETS
51010.05	LED interior lighting with wall switches and/or switch on light point in the compartments. Dimmable LED lighting in front cabin, guest cabin, saloon, aft cabin and wheelhouse.
51080.11	Luxurious LED reading lights (2x) in the front cabin
51090.11	Luxurious LED reading lights (2x) in the guest cabin
51100.01	Attractive indirect lighting in the FC, AC and in the hall to the aft cabin
51100.02	Attractive indirect lighting in the FC heads
51400.11	USB-connection in saloon (1x), dinette (1x), FC (1x), guest cabin (1x), AC (3x) and in wheelhouse (2x) for charging mobil equipment. (Total $9x$)
51500.00	1 x 12 V. socket in the saloon on Port-side, aft
51601.01	230 V. sockets in the FC ($2x$), guest cabin ($1x$), toilet FC ($1x$), guest toilet ($1x$), saloon ($4x$), galley ($1x$ double) and steering position ($1x$)
51640.01	Additional 1x double 230 V. socket in the galley
5.2 GALLE	EY
52015.01	Bar cupboard/drawer in saloon, incl. set of Linssen Yachts glasses (comprising: 6 shot glasses, 6 highball glasses, 5 whisky glasses, 6 wine glasses and 6 champagne glasses)
52020.01	Integrated waste bin in top of room divider.
52025.01	Plate holders and anti-skid mats in galley drawers
52030.01	Cutlery tray
52034.01	Pharmacy cabinet in the galley
52034.02	Pharmacy cabinet in the galley
52035.03	"Magic Corner" cupboard including basket set in saloon under the steering seat.
52040.01	80 l. refrigerator with freezer compartment under the steering bench, accessible from the galley.
52050.03	110 Ltr. refrigerator with freezer compartment in saloon
52080.03	230V. dishwasher (front loader) integrated into galley. Capacity: 6 covers
52100.02	230V. washer/dryer combination, fitted in the guest head forward cabin SB-side
52140.02	230V. induction hob, stainless steel, with touch control. 1 x 1200 W. cooking zone, 2 x 1800 W. cooking zone, 1 x 2200 W. cooking zone
52180.01	Stainless steel/corian sink
53020.03	Mixer tap in galley type Grohe Essence
52220.02	230V. stainless steel 42 l. microwave/oven/grill combination. Temperature range 30-250 degrees. 90-1000W microwave power
5.3 SANIT	TARY FITTINGS
53010.01	Selected bathroom fittings (mirror, toilet paper holder, etc.), in the forward cabin head
53012.01	Selected bathroom fittings (mirror, toilet paper holder, etc.), in guest head

53010.01	Selected bathroom fittings (mirror, toilet paper holder, etc.), in the forward cabin head
53012.01	Selected bathroom fittings (mirror, toilet paper holder, etc.), in guest head
53030.04	Build in wall mixer tap in toilet compartment FC, chrome, type Grohe Talis
53050.06	Build in wall mixer tap in forward shower type Grohe (Thermostatically adjustable) incl. shower rail
53130.02	Electric toilet in forward cabin, with fresh water rinsing
53135.02	Electric Deluxe Flush toilet, with fresh water rinsing in guest head
53130.99	"Odour system" to reduce smells from black water system

Linssen Grand Sturdy 500 Sedan

tem	Description	Page	8
5.4 A	AUDIO / VIDEO / INTERNET		
54010.0		he	
54200.0	Primary TV connection at saloon under steering position, incl. extra 230 V. socket		
54250.0	Of Glomex TV-antenna on mast, suitable for analogue & digital reception. Suitable for DVBT-T2 network.		
54400.0	43" (109cm) LED TV with integrated DVB-T2 & DVB-S tuner in saloon		
54500.0	05 Electric TV lift integrated in salon furniture, TV lift control with remote control		
5.6 II	NTERIOR UPHOLSTERY		
56041.0	O2 Anatomically moulded U-shaped saloon settee, finished in genuine leather		
56045.	Comfortable electrically horizontally adjustable Linssen Design helm seat with mat leather upholstery.	ching	
56050.0	Dashboard finished in genuine leather		
56073.2	22 2 design stools finished in genuine leather.		
56101.0	Mattrass 2x 1 pers.in front cabin type Combispring 14 cm.		
56161.0	Mattrass 2x single person in guest cabin type coldfoam 10 cm. with layer in foam in two hardness grades.		
56300.0	Beautiful pleated window covering manually operated for windows and port holes throughout the ship		
5.7 E	XTERIOR UPHOLSTERY		
57031.0	Cushion set for U-shaped cockpit settee in in water-repellent fabric, colour depend chosen interior package	ling on	
5.8 E	QUIPMENT		
58010.0	Spares kit including tool-kit, impeller, fuses, paint-tip and various maintenance par	ts	
58020.0	Complete inventory including 6 fenders, 4 mooring ropes (16 meters), boathook, li buoy, bucket, scrubbing brush, national flag, yard burgee, safety rope for anchor c and anchor ball		
58030.0	Pirst-aid box in saloon according to DIN13157		
58040.0	O1 ABC fire class compliant fire extinguishers (3 x 2 kg)		
58045.0	Optical smoke detector with fixed built-in lithium battery (life span 10 years) in all sleeping compartments.		
5.9 C	ANVAS & COVERS		
59020.3	11 Cockpit canvas Longtop, beige.		
59021.0	01 Linssen One Touch Cockpit Cover (OCC)®:		
	This electric cockpit cover, developed and patented by Linssen, can be opened all around the cockpit. By opening a zip and a few push buttons, the entire canvas (in 2 parts, SB and Port) can be opened and closed automatically by remote control. T sails disappear into the Linssen design powder-coated aluminium storage cassetted SB and Port side of the cockpit.		